

AMS-804

8M-N Hybrid XVR 4CH 6 in 1



System

Processor	Hi3520DV400
-----------	-------------

Interface

Operative Interface	Supports TRUE color 16-bit graphical interface, graphical menu and mouse interface
Preview	1 / 4

Video

Compression Coding	H.265+
Video Out	VGA; HDMI: 1024*768;1280*720;1280*1024;1440*900;1920*1080; 2560*1440(2K); 4K(3840*2160)
Preview	4*4K-N@15fps;4*5M@12fps;4*4M@15fps;4*3M@18fps;4*1080P
Encoding	4*4K-N@7fps;4*5M@6fps;4*4M@8fps;4*3M@10fps; 4*1080P@18fps
Decoding	2*4K-N@7fps;2*5M@6fps;4*4M@8fps; 4*3M@10fps; 4*1080P@18fps

Operative Mode	<p>Analog (XVI / AHD / TVI / CVI): 4*4K-N/4*5M ; 4*4M ; 4*1080P</p> <p>Hybrid: 2*4M+4*4MP IP</p> <p>Custom: allows you to set different configurations (analog + IP), respecting the device band (max 4ch)</p> <p>Network : 16*1080P;8*5M</p>
----------------	---

Alarm & Video Analysis	<p>Motion Detection (available on all channels)</p> <p>Perimeter: Cross Line - Perimeter (available on channel 1)</p> <p>Item Care: Object Missing - Object Abandoned (available on channel 1)</p> <p>Times Laps (available on all channels)</p> <p>Analysis Video (available on channel 1)</p>
------------------------	--

Human Detect	available on all channels (only with XVI Camera)
--------------	--

Audio

Audio Compression	G.711A
Intercom	Support

Record & Playback

Record Mode	Manual / Automatic / Alarm / Motion Detection /Timing
Local Playback	Depending on the settings
Search Registration	Time / Calendar / Alarm / Channel

Archiving and Backup

Video Archiving	HDD, network
Backup Mode	Network, USB

XVR 6 in 1 Main Features

- HDMI 4K (3840 x 2160)
- 4*4K-N@15fps (6in1)
- Video Compression H.265+
- Audio Compression G.711A
- HDD Sata 1,2,3 one slot up to 8TB
- Instant Playback (immediate viewing last 5 minute of record)
- Videoanalysis
- Human Detect
- Coaxial Control
- Custom Hybrid Configuration
- Send Email with picture attached
- UTC Function (manage OSD menu of cameras trough XVR)
- PPPoE, LAN,LAN WIFI DHCP & static IP,DDNS Support
- Smartphone viewing support with app XMEYE (iPhone & Android)
- ONVIF 2.4.2

External Interface

Video	4Ch BNC
Video output	1Ch VGA,1ch HDMI
Loop Vout	N/A
Audio input	1Ch
Audio output	1Ch
Alarm input	N/A
Alarm output	N/A
Network	RJ45 10M/100M
PTZ control	Coaxial Control
USB	2* USB 2.0
HDD	1*SATA (Max 8TB)
Wireless	3G, WIFI (Via USB with specific adapter)

General

Power	DC12V / 2°
Power Consumption	<15W (Without HDD)
Terms of use	Temperatura: 0°C—+55°C, Umidità:10%—90%
Dimensions	255mm*225mm*45mm
Weight	1420g

