

IP-SMP-3SF-POE

3MP Pinhole Network Camera



Technical Specification

Camera

System	Embedded RTOS,dual-core 32bit DSP(Hi3516EV200)
Image Sensor	3MP SC4239P
Video compression	H264/h264+/h265/h265++
Minimum Illumination	0,01 Lux
IR Distance	N/D
IR On/Off Control	Auto / Manual
IR LEDs	N/D

Lens

Lens Type	Pinhole Fixed Lens
Focal Length	3.7mm
Angle of View	90°
Focus Control	N/A

Video

Resolution	2304x1296
Video Output	Main stream: 2304x1296@20FSP/1920*1080@25FSP/1280@720@25fsp Sub stream: 704*576@25fps

Network

Interface	1*RJ45 10/100M adaptive port;RTSP/FTP/DHCP/NTP/UPnP
ONVIF	2.4.2
Mobile Monitor	XMEYE/XMEYE PRO (iOS,Adroid)
Detect	Human Detect / Video Analysis (cross line and intrusion area)
Noise Reduction	2D/3D
White Balance	Auto / Manual
Smart IR	Auto / Manual

Network High Defition

- 1/2.7" CMOS SC4239P 3MP
- 3 Megapixel (2304x1296)
- 3.7mm Fixed lens
- Pinhole Lens
- Human Detect / Video Analysis
- Onvif 2.4.2
- H264/H264+/H265/H265++
- IP66
- POE IEEE802.3af/DC12V

Electrical

Power Supply	12V DC ±30% / POE IEEE802.3af
Power Consumption	Max 4W

Environment

IP Protection	Internal use
---------------	--------------

Construction

Casing	Metal (Alluminium)
Dimensions / Weight	40mmx40mm / 150gr

